



**THIS** IS WHAT WE'RE  
**MADE OF**



**ARIENS**  
THE KING OF SNOW



***IT STARTS WITH A FLAKE  
AND ENDS WITH  
A FEELING***

Move this snow from here to there. Sounds like a fool's errand. Frigid, pre-dawn temps. Sidewalks buried up to 4 inches, drifting up to 14. It's easy to whine, shiver and fight it every inch of the way.

But it's a whole lot more fun to fire up an Ariens®, crack a frosty smile and send those flakes flying.

For Ariens owners, this isn't a chore. It's a chance to play in the snow.

***SO WHEN THE POWDER FLIES, AND YOUR ADRENALINE RISES,  
LET'S POWER FORWARD.***

# CONTENTS



## ARIENS PATH-PRO

|                              |         |
|------------------------------|---------|
| *Path-Pro 136R (938030)..... | Page 04 |
| *Path-Pro 136E (938034)..... | Page 06 |
| Path-Pro 208R (938031).....  | Page 08 |
| Path-Pro 208E (938032).....  | Page 10 |
| Path-Pro 208EC (938033)..... | Page 12 |



## COMPACT SERIES

|                          |         |
|--------------------------|---------|
| Compact 20 (920024)..... | Page 14 |
| Compact 24 (920021)..... | Page 16 |



## DELUXE, DELUXE EFI & DELUXE SHO SERIES

|                             |         |
|-----------------------------|---------|
| Deluxe 24 (921045).....     | Page 18 |
| Deluxe 28 (921046).....     | Page 20 |
| Deluxe 28 SHO (921048)..... | Page 22 |
| Deluxe 30 (921047).....     | Page 24 |
| Deluxe 30EFI (921049).....  | Page 26 |



## PLATINUM, PLATINUM EFI & PLATINUM SHO SERIES

|                               |         |
|-------------------------------|---------|
| Platinum 24 SHO (921050)..... | Page 28 |
| Platinum 24 EFI (921053)..... | Page 30 |
| Platinum 30 SHO (921051)..... | Page 32 |



## PROFESSIONAL & PROFESSIONAL HYDRO SERIES

|                                     |         |
|-------------------------------------|---------|
| Professional 28 (926065).....       | Page 34 |
| Professional 28 Hydro (926066)..... | Page 36 |
| Professional 32 (926071).....       | Page 38 |
| Professional 36 Hydro (926072)..... | Page 40 |



## TRACK SERIES

|                                     |         |
|-------------------------------------|---------|
| Compact Track 24 (920022).....      | Page 42 |
| Platinum Track 28 SHO (921052)..... | Page 44 |
| Hydro Pro Track 28 (926067).....    | Page 46 |



## POWER BRUSHES

|                              |         |
|------------------------------|---------|
| Power Brush 28 (921025)..... | Page 48 |
| Power Brush 36 (926062)..... | Page 49 |
| Hydro Brush 36 (926518)..... | Page 50 |

*\*Limited quantities*

# Ariens Path-Pro I36r

## Model Number: 938030

Stage Type :

Single-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 7.0  
Displacement: 136cc  
Horsepower Rating: 4.0hp  
Starter: Recoil  
Max RPM: 3600+/-100  
Fuel Tank Capacity: 2.9 qt (2.7 L)  
Fuel Shut-off: Standard  
Oil Capacity: 1.0 qt. (.473 L), 5W30

### Housing

Clearing Width: 21 in (53.3 cm)  
Housing Height: 12.2 in (31 cm)  
Construction: HDPE plastic discharge neck insert  
Auger: Reinforced Rubber, 8.375 in (21.3 cm) in diameter  
Auger Drive: Aramid Cord 6j poly V-belt  
Scraper: UHMW-PE Polymer Adjustable-cleans snow down to surface

### Drive System

Type: Semi Self-Propelled Auger Drive  
Speeds: 1 forward  
Axle System: Solid Unlocked  
Tires: 7.5 in x 1.75 in (19.1 x 4.4 cm) Semi Pneumatic Diamond Tread  
Steering: Manual

### Chute

Construction: HDPE Polymer  
Turning Radius: 210 degrees  
Rotation: Manual  
Chute Deflection: Manual  
Throwing Distance: 3 ft – 25 ft (.9-7.6 m)  
Tons per Hour: 48.00  
Capacity per minute (lbs): 1,600

### Additional Specifications

Maintenance Friendly: Easy access to engine controls and service points.  
Folding Handlebars: 1" outer diameter HRPO ASTM A513 MT1010 Tubular Steel Handlebars.  
Convenient off-season storage.  
Independent Axle: Removable, repairable axle

### Dimensions

Length: 54.3 in (137.9 cm)  
Width: 21.6 in (54.9 cm)  
Height: 40.9 in (103.9 cm)  
Weight: 87 lb (39.46 kg)  
Carton Dimensions: 35.5 x 23.5 x 23 in (90.17 x 59.69 x 58.42 cm)

### Warranty

Unit & Engine: 90 Day Limited Commercial Warranty

Ariens Path-Pro I36r  
Model Number: 938030

Optional Accessories

|                                   |          |
|-----------------------------------|----------|
| Single Stage Sno-Thro Cover ..... | 73801100 |
| Remote Chute Kit .....            | 73800800 |
| Maintenance Kit .....             | 73801000 |
| Floor Mat .....                   | 70707600 |
| High Wear Paddles .....           | 73801200 |
| Standard Paddles .....            | 53802900 |

# Ariens Path-Pro I36e

## Model Number: 938034

Stage Type :

Single-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 7.0  
Displacement: 136cc  
Horsepower Rating: 4.0 hp  
Starter: 120V/Recoil  
Max RPM: 3600+/-100  
Fuel Tank Capacity: 2.9 qt (2.7 L)  
Fuel Shut-off: Standard  
Oil Capacity: 1.0 qt (.473 L), 5W30

### Housing

Clearing Width: 21 in (53.3 cm)  
Housing Height: 12.2 in (31 cm)  
Construction: HDPE plastic discharge neck insert  
Auger: Reinforced Rubber, 8.375 in (21.3 cm) in diameter  
Auger Drive: Aramid Cord 6j poly V-belt  
Scraper: UHMW-PE Polymer Adjustable-cleans snow down to surface

### Drive System

Type: Semi Self-Propelled Auger Drive  
Speeds: 1 forward  
Axle System: Solid Unlocked  
Tires: 7.5 in x 1.75 in (19.1 x 4.4 cm) Semi Pneumatic Diamond Tread  
Steering: Manual

### Chute

Construction: HDPE Polymer  
Turning Radius: 210 degrees  
Rotation: Manual  
Chute Deflection: Manual  
Throwing Distance: 3 ft – 25 ft (.9-7.6 m)  
Tons per Hour: 48.00  
Capacity per minute (lbs): 1,600

### Additional Specifications

Maintenance Friendly: Easy access to engine controls and service points.  
Folding Handlebars: 1" outer diameter HRPO ASTM A513 MT1010 Tubular Steel Handlebars. Convenient off-season storage.  
Independent Axle: Removable, repairable axle.

### Dimensions

Length: 54.3 in (137.9 cm)  
Width: 21.6 in (54.9 cm)  
Height: 40.9 in (103.9 cm)  
Weight: 91 lb (41.28 kg)  
Carton Dimensions: 35.5 x 23.5 x 23 in (90.17 x 59.69 x 58.42 cm)

### Warranty

Unit & Engine: 90 Day Limited Commercial Warranty

**Optional Accessories**

|                                   |          |
|-----------------------------------|----------|
| Single Stage Sno-Thro Cover ..... | 73801100 |
| Remote Chute Kit .....            | 73800800 |
| Maintenance Kit .....             | 73801000 |
| Floor Mat .....                   | 70707600 |
| High wear Paddles .....           | 73801200 |
| Standard Paddles .....            | 53802900 |

# Ariens Path-Pro 208r

## Model Number: 938031

Stage Type :

Single-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: Recoil  
Max RPM: 3600+/-100  
Fuel Tank Capacity: 2.9 qt (2.7 L)  
Fuel Shut-off: Standard  
Oil Capacity: 1.0 qt (.473 L), 5W30

### Housing

Clearing Width: 21 in (53.3 cm)  
Housing Height: 12.2 in (31 cm)  
Construction: HDPE plastic discharge neck insert  
Auger: Reinforced Rubber, 8.375 in (21.3 cm) in diameter  
Auger Drive: Aramid Cord 6j poly V-belt  
Scraper: UHMW-PE Polymer Adjustable-cleans snow down to surface

### Drive System

Type: Semi Self-Propelled Auger Drive  
Speeds: 1 forward  
Axle System: Solid Unlocked  
Tires: 7.5 in x 1.75 in (19.1 cm x 4.4 cm) Semi Pneumatic Diamond Tread  
Steering: Manual

### Chute

Construction: HDPE Polymer  
Turning Radius: 210 degrees  
Rotation: Manual  
Chute Deflection: Manual  
Throwing Distance: 3 ft – 35 ft (.9m -10.7 m)  
Tons per Hour: 57.00  
Capacity per minute (lbs): 1,900

### Additional Specifications

Maintenance Friendly: Easy access to engine controls and service points.  
Folding Handlebars: 1" outer diameter HRPO ASTM A513 MT1010 Tubular Steel Handlebars. Convenient off-season storage.  
Independent Axle: Removable, repairable axle.

### Dimensions

Length: 54.3 in (137.9 cm)  
Width: 21.6 in (54.9 cm)  
Height: 40.9 in (103.9 cm)  
Weight: 91 lb (41.28 kg)  
Carton Dimension: 35.5 x 23.5 x 23 in (90.17 x 59.69 x 58.42 cm)

### Warranty

Unit & Engine: 90 Day Limited Commercial Warranty

Ariens Path-Pro 208r  
Model Number: 938031

Optional Accessories

|                                  |          |
|----------------------------------|----------|
| Single Stage Sno-Thro Cover..... | 73801100 |
| Remote Chute Kit .....           | 73800800 |
| Maintenance Kit.....             | 73801000 |
| Floor Mat .....                  | 70707600 |
| High wear Paddles .....          | 73801200 |
| Standard Paddles.....            | 53802900 |

# Ariens Path-Pro 208e

## Model Number: 938032

Stage Type :

Single-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: 120V/Recoil  
Max RPM: 3600+/-100  
Fuel Tank Capacity: 1.34 qt. (1.27 L)  
Fuel Shut-off: Standard  
Oil Capacity: 1.0 qt (.473 L), 5W30

### Housing

Clearing Width: 21 in (53.3 cm)  
Housing Height: 12.2 in (31 cm)  
Construction: HDPE plastic discharge neck insert  
Auger: Reinforced Rubber, 8.375 in (21.3 cm) in diameter  
Auger Drive: Aramid Cord 6j poly V-belt  
Scraper: UHMW-PE Polymer Adjustable-cleans snow down to surface

### Drive System

Type: Semi Self-Propelled Auger Drive  
Speeds: 1 forward  
Axle System: Solid Unlocked  
Tires: 7.5 in x 1.75 in (19.1 x 4.4 cm) Semi Pneumatic Diamond Tread  
Steering: Manual

### Chute

Construction: HDPE Polymer  
Turning Radius: 210 degrees  
Rotation: Manual  
Chute Deflection: Manual  
Throwing Distance: 3 ft – 35 ft (.9-10.7 m)  
Tons per Hour: 57.00  
Capacity per minute (lbs): 1,900

### Additional Specifications

Maintenance Friendly: Easy access to engine controls and service points.  
Folding Handlebars: 1" outer diameter HRPO ASTM A513 MT1010 Tubular Steel Handlebars. Convenient off-season storage.  
Independent Axle: Removable, repairable axle.

### Dimensions

Length: 54.3 in (137.9 cm)  
Width: 21.6 in (54.9 cm)  
Height: 40.9 in (103.9 cm)  
Weight: 95 lb (43.10 kg)  
Carton Dimensions: 35.5 x 23.5 x 23 (90.17 x 59.69 x 58.42 cm)

### Warranty

Unit & Engine: 90 Day Limited Commercial Warranty

**Optional Accessories**

|                                   |          |
|-----------------------------------|----------|
| Single Stage Sno-Thro Cover ..... | 73801100 |
| Remote Chute Kit .....            | 73800800 |
| Maintenance Kit .....             | 73801000 |
| Floor Mat .....                   | 70707600 |
| High wear Paddles .....           | 73801200 |
| Standard Paddles .....            | 53802900 |

# Ariens Path-Pro 208ec

## Model Number: 938033

Stage Type :

Single-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: 120V/Recoil  
Max RPM: 3600+/-100  
Fuel Tank Capacity: 1.34 qt (1.27 L)  
Fuel Shut-off: Standard  
Oil Capacity: 1.0 pt (.473 L), 5W30

### Housing

Clearing Width: 21 in (53.3 cm)  
Housing Height: 12.2 in (31 cm)  
Construction: HDPE plastic discharge neck insert  
Auger: Reinforced Rubber, 8.375 in (21.3 cm) in diameter  
Auger Drive: Aramid Cord 6j poly V-belt  
Scraper: UHMW-PE Polymer Adjustable-cleans snow down to surface

### Drive System

Type: Semi Self-Propelled Auger Drive  
Speeds: 1 forward  
Axle System: Solid Unlocked  
Tires: 7.5 in x 1.75 in (19.1 x 4.4 cm) Semi Pneumatic Diamond Tread  
Steering: Manual

### Chute

Construction: HDPE Polymer  
Turning Radius: 210 degrees  
Rotation: Remote  
Chute Deflection: Manual  
Throwing Distance: 3 ft – 35 ft (.9-10.7 m)  
Tons per Hour: 57.00  
Capacity per minute (lbs): 1,900

### Additional Specifications

Maintenance Friendly: Easy access to engine controls and service points.  
Folding Handlebars: 1" outer diameter HRPO ASTM A513 MT1010 Tubular Steel Handlebars. Convenient off-season storage.  
Independent Axle: Removable, repairable axle.

### Dimensions

Length: 54.3 in (137.9 cm)  
Width: 21.6 in (54.9 cm)  
Height: 40.9 in (103.9 cm)  
Weight: 97 lb (44.00kg)  
Carton Dimension: 35.5 x 23.5 x 23 in (90.17 x 59.69 x 58.42 cm)

### Warranty

Unit & Engine: 90 Day Limited Commercial Warranty

Ariens Path-Pro 208ec  
Model Number: 938033

Optional Accessories

|                                   |          |
|-----------------------------------|----------|
| Single Stage Sno-Thro Cover ..... | 73801100 |
| Remote Chute Kit .....            | 73800800 |
| Maintenance Kit .....             | 73801000 |
| Floor Mat .....                   | 70707600 |
| High wear Paddles .....           | 73801200 |
| Standard Paddles .....            | 53802900 |

## Compact 20

Model Number: 920024

Stage Type: Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-100  
Fuel Tank Capacity: 1.5 QT. (1.4 l)  
Fuel Shut-off: Standard  
Oil Capacity: 16 oz, 5W30

### Housing

Clearing Width: 20 in (50.8 cm)  
Housing Height: 20 in (50.8 cm)  
Construction: 16 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 12 in (30.5 cm) in diameter, 1190 RPM, tip speed of 62.3 ft/sec (19.0 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 11 in (27.9 cm) in diameter  
Auger Drive: Single HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Pin Lock  
Tires: 15 in x 5 in (38 x 13 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 205 degrees  
Rotation: 2.5x Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 40 ft (.9-12.2 m)  
Tons per Hour: 54.46  
Capacity per minute (lbs): 1,815

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Folding Handlebars: Tubular Steel Handlebars. Convenient off-season storage.

### Dimensions

Length: 53.3 in (135.4 cm)  
Width: 22.4 in (56.9 cm)  
Height: 44 in (111.8 cm)  
Weight: 181.1 lb (82.1 kg)  
Carton Dimensions: 44.5 x 27 x 34.25 in (113.03 x 68.58 x 86.9 cm)

# Compact 20

Model Number: 920024

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                        |          |
|----------------------------------------|----------|
| Compact Sno-Thro Cover .....           | 72601400 |
| Ariens Branded Snow Cab .....          | 72102600 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Black Drift Cutter Kit .....           | 73203100 |
| Ariens Steel Skid Shoe Kit .....       | 72101100 |
| Non-Abrasive Skid Shoe Kit .....       | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72000800 |
| Protective Floor Mat – 30" x 36" ..... | 70707600 |
| Handwarmer Accessory Kit .....         | 72101400 |
| Snow Tire Chains (15" x 5" x 6") ..... | 72101600 |
| Shear Bolt with Nut .....              | 53200500 |

# Compact 24

Model Number: 920021

Stage Type: Two-Stage

## Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-100  
Fuel Tank Capacity: 1.5 QT. (1.4 l)  
Fuel Shut-off: Standard  
Oil Capacity: 16 oz, 5W30

## Housing

Clearing Width: 24 in (60.1 cm)  
Housing Height: 20 in (50.8 cm)  
Construction: 16 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 12 in (30.5 cm) in diameter, 1190 RPM, tip speed of 62.3 ft/sec (19.0 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 11 in (27.9 cm) in diameter  
Auger Drive: Single HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

## Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Pin Lock  
Tires: 15 in x 5 in (38 x 13 cm) Directional Snow Tread

## Chute

Construction: Steel  
Turning Radius: 205 degrees  
Rotation: 2.5x Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 40 ft (.9-12.2 m)  
Tons per Hour: 57.66  
Capacity per minute (lbs): 1,922

## Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Folding Handlebars: Tubular Steel Handlebars. Convenient off-season storage.

## Dimensions

Length: 53.3 (135.4 cm)  
Width: 26.4 in (67.0 cm)  
Height: 44 in (111.8 cm)  
Weight: 183.1 lb (83.1 cm)  
Carton Dimensions: 48 x 27.5 x 35 in (113.03 x 69.85 x 87 cm)

# Compact 24

Model Number: 920021

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                        |          |
|----------------------------------------|----------|
| Compact Sno-Thro Cover .....           | 72601400 |
| Ariens Branded Snow Cab .....          | 72102600 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Black Drift Cutter Kit .....           | 73203100 |
| Ariens Steel Skid Shoe Kit .....       | 72101100 |
| Non-Abrasive Skid Shoe Kit .....       | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72000800 |
| Protective Floor Mat – 30" x 36" ..... | 70707600 |
| Handwarmer Accessory Kit .....         | 72101400 |
| Snow Tire Chains (15" x 5" x 6") ..... | 72101600 |
| Shear Bolt with Nut .....              | 53200500 |

# Deluxe 24

## Model Number: 921045

Stage Type : Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 12.5  
Displacement: 254cc  
Horsepower Rating: 7.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 2.9 qt (2.7 L)  
Fuel Shut-off: Standard  
Oil Capacity: 20 oz, 5W30

### Housing

Clearing Width: 24 in (60.1 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 14 in (35.6 cm) in diameter, 1063 RPM, tip speed of 64.98 ft/sec (19.8 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: 2.5x Ice Drill  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 50 ft (.9-15.2 m)  
Tons per Hour: 61.80  
Capacity per minute (lbs): 2,060

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.  
Assembled in the U.S.A.

### Dimensions

Length: 58.6 in (148.8 cm)  
Width: 26.4 in (67.1 cm)  
Height: 45.3 in (115.1 cm)  
Weight: 245.5 lbs (111.4 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Deluxe 24

Model Number: 921045

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 28" Rotary Snow Brush.....            | 82100100 |
| Sno-Thro Cover.....                   | 72601400 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Ariens Steel Skid Shoe Kit.....       | 72101100 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Handwarmer Accessory Kit.....         | 72101400 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Track Drive Conversion Kit.....       | 72102800 |
| Black Shear Bolt with Nut.....        | 52100100 |

# Deluxe 28

## Model Number: 921046

Stage Type : Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 12.5  
Displacement: 254cc  
Horsepower Rating: 7.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 2.9 qt (2.7 L)  
Fuel Shut-off: Standard  
Oil Capacity: 20 oz, 5W30

### Housing

Clearing Width: 28 in (71.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 14 in (35.6 cm) in diameter, 1063 RPM, tip speed of 64.98 ft/sec (19.8 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: 2.5x Ice Drill  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 50 ft (.9-15.2 m)  
Tons per Hour: 65.2 tons per hour  
Capacity per minute (lbs): 2,173 lbs/min

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.

### Dimensions

Length: 58.6 in (148.8 cm)  
Width: 29.9 in (75.9 cm)  
Height: 45.3 in (115.1 cm)  
Weight: 249.8 lbs (113.3 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Deluxe 28

Model Number: 921046

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                            |          |
|--------------------------------------------|----------|
| Sno-Thro Cover. ....                       | 72601500 |
| 10 lb. Front Weight Kit . . . . .          | 72406500 |
| Ariens Branded Snow Cab . . . . .          | 72102600 |
| Orange Drift Cutter Kit. . . . .           | 72406900 |
| Ariens Steel Skid Shoe Kit . . . . .       | 72101100 |
| Non-Abrasive Skid Shoe Kit . . . . .       | 72600300 |
| Sno-Thro Maintenance Kit . . . . .         | 72101300 |
| Protective Floor Mat – 30" x 36" . . . . . | 70707600 |
| Handwarmer Accessory Kit . . . . .         | 72101400 |
| Snow Tire Chains (16" x 8"). . . . .       | 72601800 |
| Track Drive Conversion Kit . . . . .       | 72102800 |
| Black Shear Bolt with Nut . . . . .        | 52100100 |

# Deluxe 28 SHO

## Model Number: 921048

Stage Type: Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 15  
Displacement: 306cc  
Horsepower Rating: 9 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 1.3 qy (1.2 L)  
Fuel Shut-off: Standard  
Oil Capacity: 32 oz, 5W30

### Housing

Clearing Width: 28 in (71.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, 3 Blade Profile, Super High Output Impeller, 14 in (35.6 cm) in diameter, 1083 RPM, tip speed of 66.2 ft/sec (20.2 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: 2.5x Ice Drill  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 55 ft (.9-16.76 m)  
Tons per Hour: 72.22  
Capacity per minute (lbs): 2,407

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.

### Dimensions

Length: 58.6 in (148.8 cm)  
Width: 29.9 in (75.9 cm)  
Height: 45.3 (115.1 cm)  
Weight: 267.5 lb (121.3 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Deluxe 28 SHO

Model Number: 921048

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                            |          |
|--------------------------------------------|----------|
| Large Sno-Thro Cover . . . . .             | 72601500 |
| 10 lb. Front Weight Kit . . . . .          | 72406500 |
| Ariens Branded Snow Cab . . . . .          | 72102600 |
| Orange Drift Cutter Kit. . . . .           | 72406900 |
| Ariens Steel Skid Shoe Kit . . . . .       | 72101100 |
| Non-Abrasive Skid Shoe Kit . . . . .       | 72600300 |
| Sno-Thro Maintenance Kit . . . . .         | 72101300 |
| Protective Floor Mat – 30" x 36" . . . . . | 70707600 |
| Handwarmer Accessory Kit . . . . .         | 72101400 |
| Snow Tire Chains (16" x 8") . . . . .      | 72601800 |
| Track Drive Conversion Kit . . . . .       | 72102800 |
| Black Shear Bolt with Nut . . . . .        | 52100100 |
| 28" Rotary Snow Brush . . . . .            | 82100100 |

## Deluxe 30

Model Number: 921047

Stage Type: Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 15.0  
Displacement: 306cc  
Horsepower Rating: 9.0 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 1.3 qt (1.2 L)  
Fuel Shut-off: Standard  
Oil Capacity: 32 oz, 5W30

### Housing

Clearing Width: 30 in (76.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1083 RPM, tip speed of 66.2 ft/sec (20.2 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: 2.5x Ice Drill  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 50 ft (.9-15.2 m)  
Tons per Hour: 70.61  
Capacity per minute (lbs): 2,354

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.  
Handwarmers: Standard

### Dimensions

Length: 58.8 in (148.1 cm)  
Width: 32.4 in (82.3 cm)  
Height: 45.5 in (115.6 cm)  
Weight: 275.6 lb (125.0 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Deluxe 30

Model Number: 921047

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                        |          |
|----------------------------------------|----------|
| Large Sno-Thro Cover.....              | 72601500 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Ariens Branded Snow Cab .....          | 72102600 |
| Orange Drift Cutter Kit.....           | 72406900 |
| Ariens Steel Skid Shoe Kit.....        | 72101100 |
| Non-Abrasive Skid Shoe Kit.....        | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72101300 |
| Protective Floor Mat – 36" x 36" ..... | 70706700 |
| Handwarmer Accessory Kit .....         | 72101400 |
| Snow Tire Chains (16" x 8") .....      | 72601800 |
| Track Drive Conversion Kit .....       | 72102800 |
| Black Shear Bolt with Nut .....        | 52100100 |

## Deluxe 30 EFI

Model Number: 921049

Stage Type:

Two-Stage

### Engine

Brand: Ariens AX EZ-Launch EFI  
Type: 4-Stroke  
Ft-Lbs: 15.0  
Displacement: 306cc  
Horsepower Rating: 9.0 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 3.2 qt (3.0 L)  
Fuel Shut-off: Automatic with on/off key  
Oil Capacity: 32 oz, 5W30

### Housing

Clearing Width: 30 in (76.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 14 in (35.6 cm) in diameter, 1063 RPM, tip speed of 64.98 ft/sec (19.8 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: 2.5x Ice Drill  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 50 ft (.9-15.2 m)  
Tons per Hour: 70.61  
Capacity per minute (lbs): 2,354

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Folding Handlebars: Tubular Steel Handlebars. Convenient off-season storage.  
Handwarmers: Standard

### Dimensions

Length: 58.3 in (148.1 cm)  
Width: 32.4 in (82.3 cm)  
Height: 45.5 in (115.6 cm)  
Weight: 275.6 lbs (125 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Deluxe 30 EFI

Model Number: 921049

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                        |          |
|----------------------------------------|----------|
| Large Sno-Thro Cover.....              | 72601500 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Ariens Branded Snow Cab .....          | 72102600 |
| Orange Drift Cutter Kit.....           | 72406900 |
| Ariens Steel Skid Shoe Kit.....        | 72101100 |
| Non-Abrasive Skid Shoe Kit.....        | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72101300 |
| Protective Floor Mat – 36" x 36" ..... | 70706700 |
| Handwarmer Accessory Kit .....         | 72101400 |
| Snow Tire Chains (16" x 8") .....      | 72601800 |
| Track Drive Conversion Kit .....       | 72102800 |
| Black Shear Bolt with Nut .....        | 52100100 |

# Platinum 24 SHO

## Model Number: 921050

Stage Type: Two-Stage

### Engine

Brand: Ariens AX  
 Type: 4-Stroke  
 Ft-Lbs: 17.0  
 Displacement: 369cc  
 Horsepower Rating: 10.5 hp  
 Starter: 120V/Recoil  
 High Idle – RPM (min): 3600+/-100  
 Fuel Tank Capacity: 3.2 qt (3.0 L)  
 Fuel Shut-off: Standard  
 Oil Capacity: 38 oz, 5W30

### Housing

Clearing Width: 24 in (60.1 cm)  
 Housing Height: 21 in (53.3 cm)  
 Construction: 14 Gauge Steel  
 Impeller: 12 Gauge Steel, 3 Blade Profile, Super High Output impeller, 14 in (35.6 cm) in diameter, 1142 RPM, tip speed of 69.76 ft/sec (21.3 m/s)  
 Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
 Auger Drive: Dual HA Belt Drive  
 Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
 Speeds: 6 forward/2 reverse  
 Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
 Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
 Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
 Turning Radius: 200 degrees  
 Rotation: Quick Turn  
 Chute Deflection: Remote  
 Throwing Distance: 3 ft - 55 ft. (.9 - 16.76 m)  
 Tons per Hour: 72.81  
 Capacity per minute (lbs): 2,427

### Additional Specifications

Skid Shoes: Steel, Reversible  
 Headlight: In-dash halogen  
 One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
 Folding Handlebars: Tubular Steel Handlebars.  
 Handwarmers: Standard

### Dimensions

Length: 58.3 in (148.1 cm)  
 Width: 26.4 in (67.06 cm)  
 Height: 45.9 in (116.6 cm)  
 Weight: 286 lb (129.7 kg)  
 Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

Platinum 24 SHO  
Model Number: 921050

Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 28" Rotary Snow Brush.....            | 82100100 |
| Sno-Thro Cover.....                   | 72601400 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Ariens Steel Skid Shoe Kit.....       | 72101100 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Shear Bolt with Nut.....              | 52100100 |
| Track Drive Conversion Kit.....       | 72102800 |

# Platinum 24 EFI

## Model Number: 921053

Stage Type: Two-Stage

### Engine

Brand: Ariens AX EZ-Launch EFI  
Type: 4-Stroke  
Ft-Lbs: 17.0  
Displacement: 369cc  
Horsepower Rating: 10.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 3.2 qt (3.0 L)  
Fuel Shut-off: Automatic with on/off key  
Oil Capacity: 38 oz, 5W30

### Housing

Clearing Width: 24 in (60.1 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 14 in (30.5 cm) in diameter, 1142 RPM, tip speed of 69.76 ft/sec (21.3 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft - 55 ft. (.9 - 16.7 m)  
Tons per Hour: 72.81  
Capacity per minute (lbs): 2,427

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive  
Folding Handlebars: Tubular Steel Handlebars. Convenient off-season storage.  
Handwarmers: Standard

### Dimensions

Length: 58.3 in (148.1 cm)  
Width: 26.4 in (67.06 cm)  
Height: 45.9 in (116.6 cm)  
Weight: 273 lbs (123.8 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Platinum 24 EFI

Model Number: 921053

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 28" Rotary Snow Brush.....            | 82100100 |
| Sno-Thro Cover.....                   | 72601400 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Ariens Steel Skid Shoe Kit.....       | 72101100 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Shear Bolt with Nut.....              | 52100100 |
| Track Drive Conversion Kit.....       | 72102800 |

# Platinum 30 SHO

## Model Number: 921051

Stage Type: Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 20.0  
Displacement: 414cc  
Horsepower Rating: 12.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 3.2 qt (3.0 L)  
Fuel Shut-off: Standard  
Oil Capacity: 38 oz, 5W30

### Housing

Clearing Width: 30 in (76.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, 3 Blade Profile, Super High Output impeller, 14 in (35.6 cm) in diameter, 1083 RPM, tip speed of 66.2 ft/sec (20.2 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft - 55 ft. (.9 - 16.76 m)  
Tons per Hour: 82.3  
Capacity per minute (lbs): 2,743

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.  
Handwarmers: Standard

### Dimensions

Length: 58.3 in (148.1 cm)  
Width: 32.4 in (82.3 cm)  
Height: 45.9 in (116.6 cm)  
Weight: 293.8 lb (133.3 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Platinum 30 SHO

Model Number: 921051

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 28" Rotary Snow Brush.....            | 82100100 |
| Large Sno-Thro Cover.....             | 72601500 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Ariens Steel Skid Shoe Kit.....       | 72101100 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 36" x 36"..... | 70706700 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Track Drive Conversion Kit.....       | 72102800 |
| Black Shear Bolt with Nut.....        | 52100100 |

# Professional 28

## Model Number: 926065

Stage Type :

Two-Stage

### Engine

Brand: Ariens Polar Force Pro by Briggs & Stratton  
Type: 4-Stroke  
Ft-Lbs: 21.0  
Displacement: 420cc  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-100  
Fuel Tank Capacity: 5.9 qt (5.6 L)  
Fuel Shut-off: Standard  
Oil Capacity: 37 oz, 5W30

### Housing

Clearing Width: 28 in (71.2 cm)  
Housing Height: 23.5 in (59.7 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1112 RPM, tip speed of 67.9 ft/sec (20.7 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 16 in (40.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 11 Gauge Steel made of Boron, adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft - 60 ft. (.9 - 18.28 m)  
Tons per Hour: 79.04  
Capacity per minute (lbs): 2,635

### Additional Specifications

Skid Shoes: Reversible Commercial Skids, heat treated, 0.5 in wear edge  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Heavy-duty commercial handlebars, welded from rectangular 2"x1.5", 14 ga steel tubing.  
Handwarmers: Standard

### Dimensions

Length: 60.3 in (153.2 cm)  
Width: 30.2 (76.7 cm)  
Height: 46.6 in (118.4 cm)  
Weight: 339/1 lb (153.8 kg)  
Carton Dimensions: 45.5 x 33 x 41 in (115.57 x 83.82 x 104.14 cm)

### Warranty

Unit & Engine: 1 Year Limited Commercial Warranty  
Gear Case: 5 Year Limited Commercial Warranty

# Professional 28

Model Number: 926065

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 36" Rotary Snow Brush.....            | 82600300 |
| Track Drive Conversion Kit.....       | 72602900 |
| Large Sno-Thro Cover.....             | 72601500 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Black Shear Bolt with Nut.....        | 52100100 |
| Orange Drift Cutter Kit.....          | 72406900 |

# Professional 28 Hydro

## Model Number: 926066

Stage Type:

Two-Stage

### Engine

Brand: Ariens Polar Force Pro by Briggs & Stratton  
Type: 4-Stroke  
Ft-Lbs: 21.0  
Displacement: 420cc  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-100  
Fuel Tank Capacity: 5.9 qt (5.6 L)  
Fuel Shut-off: Standard  
Oil Capacity: 37 oz, 5W30

### Housing

Clearing Width: 28 in (71.2 cm)  
Housing Height: 23.5 in (59.7 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1112 RPM, tip speed of 67.9 ft/sec (20.7 m/s)  
Auger: 12 Gauge Steel, Serrated Type, 16 in (40.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 11 Gauge Steel made of Boron, adjustable

### Drive System

Type: Hydrostatic, Hydro-Gear® RT-310™ transmission with synthetic oil  
Speeds: Infinitely Variable  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, Automatic mechanical transmission  
Tires: 16 in x 4.8 in (41 x 12 cm) Directional Snow Tread

### Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft - 60 ft. (.9 - 18.28 m)  
Tons per Hour: 79.04  
Capacity per minute (lbs): 2,635

### Additional Specifications

Skid Shoes: Reversible Commercial Skids, heat treated, 0.5 in wear edge  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Heavy-duty commercial handlebars, welded from rectangular 2"x1.5", 14 ga steel tubing.  
Handwarmers: Standard

### Dimensions

Length: 60.3 in (153.2 cm)  
Width: 30.2 in (76.7 cm)  
Height: 46.6 in (118.4 cm)  
Weight: 352 lb (159.7 cm)  
Carton Dimensions: 45.5 x 33 x 41 in (115.57 x 83.82 x 104.14 cm)

### Warranty

Unit & Engine: 1 Year Limited Commercial Warranty  
Gear Case: 5 Year Limited Commercial Warranty

# Professional 28 Hydro

Model Number: 926066

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 36" Rotary Snow Brush.....            | 82600300 |
| Large Sno-Thro Cover.....             | 72602900 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Snow Tire Chains (16" x 8").....      | 72601800 |
| Black Shear Bolt with Nut.....        | 52100100 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Track Drive Conversion Kit.....       | 72602900 |

# Professional 32

## Model Number: 926071

Stage Type:

Two-Stage

### Engine

Brand:

Ariens Polar Force Pro by Briggs & Stratton

Type:

4-Stroke

Ft-Lbs:

21.0

Displacement:

420cc

Starter:

120V/Recoil

High Idle – RPM (min):

3600+/-100

Fuel Tank Capacity:

5.9 qt (5.6 L)

Fuel Shut-off:

Standard

Oil Capacity:

37 oz, 5W30

### Housing

Clearing Width:

32 in (81.3 cm)

Housing Height:

23.5 in (59.7 cm)

Construction:

14 Gauge Steel

Impeller:

12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1112 RPM, tip speed of 67.9 ft/sec (20.7 m/s)

Auger:

12 Gauge Steel, Serrated Type, 16 in (40.6 cm) in diameter

Auger Drive:

Dual HA Belt Drive

Scraper:

11 Gauge Steel made of Boron, adjustable

### Drive System

Type:

Disc-O-Matic

Speeds:

6 forward/2 reverse

Gear Case:

Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil

Axle System/Steering:

Auto-Turn steering technology, Automatic mechanical transmission

Tires:

16 in x 6.5 in (41 x 17 cm) Directional Snow Tread

### Chute

Construction:

Steel

Turning Radius:

200 degrees

Rotation:

Quick Turn

Chute Deflection:

Remote

Throwing Distance:

3 ft - 60 ft. (.9 - 18.28 m)

Tons per Hour:

90.33

Capacity per minute (lbs):

3,011

### Additional Specifications

Skid Shoes:

Reversible Commercial Skids, heat treated, 0.5 in wear edge

Headlight:

In-dash halogen

One Hand Interlock:

Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.

Handlebars:

Heavy-duty commercial handlebars, welded from rectangular 2"x1.5", 14 ga steel tubing.

Handwarmers:

Standard

### Dimensions

Length:

60.3 (153.2 cm)

Width:

34.5 in (87.6 cm)

Height:

46.6 in (118.4 cm)

Weight:

333.6 lbs (151.3 kg)

Carton Dimensions:

45.5 x 41 x 41 in (115.57 x 104.14 x 104.14 cm)

### Warranty

Unit & Engine:

1 Year Limited Commercial Warranty

Gear Case:

5 Year Limited Commercial Warranty

**Optional Accessories**

|                                        |          |
|----------------------------------------|----------|
| Track Drive Conversion Kit .....       | 72602900 |
| Large Sno-Thro Cover. ....             | 72601500 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Ariens Branded Snow Cab .....          | 72102600 |
| Non-Abrasive Skid Shoe Kit .....       | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72101300 |
| Protective Floor Mat – 36" x 36" ..... | 70706700 |
| Snow Tire Chains (16" x 8") .....      | 72601800 |
| Black Shear Bolt with Nut .....        | 52100100 |
| Orange Drift Cutter Kit. ....          | 72406900 |

# Professional 36 Hydro

## Model Number: 926072

Stage Type:

Two-Stage

### Engine

Brand:

Ariens Polar Force Pro by Briggs & Stratton

Type:

4-Stroke

Ft-Lbs:

21.0

Displacement:

420cc

Starter:

120V/Recoil

High Idle – RPM (min):

3600+/-100

Fuel Tank Capacity:

5.9 qt (5.6 L)

Fuel Shut-off:

Standard

Oil Capacity:

37 oz, 5W30

### Housing

Clearing Width:

36 in (91.4 cm)

Housing Height:

23.5 in (59.7 cm)

Construction:

14 Gauge Steel

Impeller:

12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1112 RPM, tip speed of 67.9 ft/sec (20.7 m/s)

Auger:

12 Gauge Steel, Serrated Type, 16 in (40.6 cm) in diameter

Auger Drive:

Dual HA Belt Drive

Scraper:

11 Gauge Steel made of Boron, adjustable

### Drive System

Type:

Hydrostatic, Hydro-Gear® RT-310™ transmission with synthetic oil

Speeds:

Infinitely Variable

Gear Case:

Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil

Axle System/Steering:

Auto-Turn steering technology, Automatic mechanical transmission

Tires:

16 in x 6.5 in (41 x 17 cm) Directional Snow Tread

### Chute

Construction:

Steel

Turning Radius:

200 degrees

Rotation:

Quick Turn

Chute Deflection:

Remote

Throwing Distance:

3 ft - 60 ft. (.9 - 18.28 m)

Tons per Hour:

101.62

Capacity per minute (lbs):

3,387

### Additional Specifications

Skid Shoes:

Reversible Commercial Skids, heat treated, 0.5 in wear edge

Headlight:

In-dash halogen

One Hand Interlock:

Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.

Handlebars:

Heavy-duty commercial handlebars, welded from rectangular 2"x1.5", 14 ga steel tubing.

Handwarmers:

Standard

### Dimensions

Length:

60.3 in (153.2 cm)

Width:

38.2 in (97 cm)

Height:

46.6 cm (118.4 cm)

Weight:

353 lb (160.1 kg)

Carton Dimensions:

45.5 x 41 x 41 in (115.57 x 104.14 x 104.14 cm)

### Warranty

Unit & Engine:

1 Year Limited Commercial Warranty

Gear Case:

5 Year Limited Commercial Warranty

**Optional Accessories**

|                                       |          |
|---------------------------------------|----------|
| Large Sno-Thro Cover. ....            | 72601500 |
| 10 lb. Front Weight Kit ....          | 72406500 |
| Ariens Branded Snow Cab ....          | 72102600 |
| Non-Abrasive Skid Shoe Kit ....       | 72600300 |
| Sno-Thro Maintenance Kit ....         | 72101300 |
| Protective Floor Mat – 36" x 36" .... | 70706700 |
| Snow Tire Chains (16" x 8") ....      | 72601800 |
| Shear Bolt with Nut. ....             | 52100100 |
| Orange Drift Cutter Kit. ....         | 72406900 |
| Track Drive Conversion Kit ....       | 72602900 |

# Compact Track 24

## Model Number: 920022

Stage Type : Two-Stage

### Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 9.5  
Displacement: 208cc  
Horsepower Rating: 6.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-100  
Fuel Tank Capacity: 1.5 qt (1.4 L)  
Fuel Shut-off: Standard  
Oil Capacity: 16 oz, 5W30

### Housing

Clearing Width: 24 in (60.1 cm)  
Housing Height: 20 in (50.8 cm)  
Construction: 16 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, 12 in (30.5 cm) in diameter, 1190 RPM, tip speed of 62.3 ft/sec (19.0 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 11 in (27.9 cm) in diameter  
Auger Drive: Single HA Belt Drive  
Scraper: 10 Gauge Steel, adjustable

### Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Solid Locked  
Tires: 5.5 in Wide Directional Snow Track

### Chute

Construction: Steel  
Turning Radius: 205 degrees  
Rotation: 2.5x Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 40 ft (.9-12.2 m)  
Tons per Hour: 57.66  
Capacity per minute (lbs): 1,922

### Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Folding Handlebars: Tubular Steel Handlebars. Convenient off-season storage.  
Housing: 5 position height control

### Dimensions

Length: 53.3 in (135.4 cm)  
Width: 26.4 in (67.06 cm)  
Height: 43.4 in (110.2 cm)  
Weight: 220 lbs (99.8 cm)  
Carton Dimensions: 48 x 27.5 x 35 in (121.92 x 69.85 x 88.9 cm)

# Compact Track 24

Model Number: 920022

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                        |          |
|----------------------------------------|----------|
| Compact Sno-Thro Cover .....           | 72601400 |
| Ariens Branded Snow Cab .....          | 72102600 |
| 10 lb. Front Weight Kit .....          | 72406500 |
| Black Drift Cutter Kit .....           | 73203100 |
| Ariens Steel Skid Shoe Kit .....       | 72101100 |
| Non-Abrasive Skid Shoe Kit .....       | 72600300 |
| Sno-Thro Maintenance Kit .....         | 72000800 |
| Protective Floor Mat – 30" x 36" ..... | 70707600 |
| Handwarmer Accessory Kit .....         | 72101400 |
| Shear Bolt with Nut .....              | 53200500 |

# Platinum Track 28 SHO

Model Number: 921052

Stage Type: Two-Stage

## Engine

Brand: Ariens AX  
Type: 4-Stroke  
Ft-Lbs: 17  
Displacement: 369cc  
Horsepower Rating: 10.5 hp  
Starter: 120V/Recoil  
High Idle – RPM (min): 3600+/-50  
Fuel Tank Capacity: 3.2 qt (3.0 L)  
Fuel Shut-off: Standard  
Oil Capacity: 38 oz, 5W30

## Housing

Clearing Width: 28 in (71.2 cm)  
Housing Height: 21 in (53.3 cm)  
Construction: 14 Gauge Steel  
Impeller: 12 Gauge Steel, Steel 3 Blade Profile, Super High Output Impeller, 14 in (35.6 cm) in diameter, 1083 RPM, tip speed of 66.2 ft/sec (20.2 m/s)  
Auger: 12 Gauge Steel, Steel Serrated Type, 14 in (35.6 cm) in diameter  
Auger Drive: Dual HA Belt Drive  
Scraper: 10 Gauge Steel, adjustable

## Drive System

Type: Disc-O-Matic  
Speeds: 6 forward/2 reverse  
Gear Case: Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil  
Axle System/Steering: Auto-Turn steering technology, automatic mechanical transmission  
Tires: 5.5 in Wide Directional Snow Track

## Chute

Construction: Steel  
Turning Radius: 200 degrees  
Rotation: Quick Turn  
Chute Deflection: Remote  
Throwing Distance: 3 ft – 55 ft (.9-16.76 m)  
Tons per Hour: 76.81  
Capacity per minute (lbs): 2,560

## Additional Specifications

Skid Shoes: Steel, Reversible  
Headlight: In-dash halogen  
One Hand Interlock: Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive.  
Handlebars: Tubular Steel Handlebars.  
Housing: 5 position height control  
Handwarmers: Standard

## Dimensions

Length: 58.5 in (148.6 cm)  
Width: 29.9 in (75.9 cm)  
Height: 45.3 in (115.1 cm)  
Weight: 306.3 lb (138.9 kg)  
Carton Dimensions: 51.5 x 32 x 35 in (130.81 x 81.28 x 88.9 cm)

# Platinum Track 28 SHO

Model Number: 921052

## Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 90 Day Limited Commercial Warranty |
| Gear Case:     | 1 Year Limited Commercial Warranty |

## Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| 28" Rotary Snow Brush.....            | 82100100 |
| Large Sno-Thro Cover.....             | 72601500 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Orange Drift Cutter Kit.....          | 72406900 |
| Ariens Steel Skid Shoe Kit.....       | 72101100 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30" x 36"..... | 70707600 |
| Black Shear Bolt with Nut.....        | 52100100 |

# Hydro Pro Track 28

## Model Number: 926072

|                                  |                                                                                                                 |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Stage Type :                     | Two-Stage                                                                                                       |
| <b>Engine</b>                    |                                                                                                                 |
| Brand:                           | Ariens Polar Force Pro by Briggs & Stratton                                                                     |
| Type:                            | 4-Stroke                                                                                                        |
| Ft-Lbs:                          | 21.0                                                                                                            |
| Displacement:                    | 420cc                                                                                                           |
| Starter:                         | 120V/Recoil                                                                                                     |
| High Idle – RPM (min):           | 3600+/-100                                                                                                      |
| Fuel Tank Capacity:              | 5.9 qt (5.6 L)                                                                                                  |
| Fuel Shut-off:                   | Standard                                                                                                        |
| Oil Capacity:                    | 37 oz, 5W30                                                                                                     |
| <b>Housing</b>                   |                                                                                                                 |
| Clearing Width:                  | 28 in (71.2 cm)                                                                                                 |
| Housing Height:                  | 23.5 in (59.7 cm)                                                                                               |
| Construction:                    | 14 Gauge Steel                                                                                                  |
| Impeller:                        | 12 Gauge Steel, 3 Blade Profile, 14 in (35.6 cm) in diameter, 1112 RPM, tip speed of 67.9 ft/sec (20.7 m/s)     |
| Auger:                           | 12 Gauge Steel, Serrated Type, 16 in (40.6 cm) in diameter                                                      |
| Auger Drive:                     | Dual HA Belt Drive                                                                                              |
| Scraper:                         | 11 Gauge Steel made of Boron, adjustable                                                                        |
| <b>Drive System</b>              |                                                                                                                 |
| Type:                            | Hydrostatic, Hydro-Gear® RT-310™ transmission with synthetic oil                                                |
| Speeds:                          | Infinitely Variable                                                                                             |
| Gear Case:                       | Top Load, Cast Iron Gear Case with alloy steel gears, L-3 synthetic severe-duty gear oil                        |
| Axle System/Steering:            | Auto-Turn steering technology, Automatic mechanical transmission                                                |
| Tires:                           | 5.5 in Wide Directional Snow Track                                                                              |
| <b>Chute</b>                     |                                                                                                                 |
| Construction:                    | Steel                                                                                                           |
| Turning Radius:                  | 200 degrees                                                                                                     |
| Rotation:                        | Quick Turn                                                                                                      |
| Chute Deflection:                | Remote                                                                                                          |
| Throwing Distance:               | 3 ft - 60 ft. (.9 - 18.28 m)                                                                                    |
| Tons per Hour:                   | 79.04                                                                                                           |
| Capacity per minute (lbs):       | 2,635                                                                                                           |
| <b>Additional Specifications</b> |                                                                                                                 |
| Skid Shoes:                      | Reversible Commercial Skids, heat treated, 0.5 in wear edge                                                     |
| Headlight:                       | In-dash halogen                                                                                                 |
| One Hand Interlock:              | Allows the operator to move their hand to the chute control without disengaging the wheel drive or auger drive. |
| Handlebars:                      | Heavy-duty commercial handlebars, welded from rectangular 2"x1.5", 14 ga steel tubing.                          |
| Housing:                         | 5 position height control                                                                                       |
| <b>Dimensions</b>                |                                                                                                                 |
| Length:                          | 60.3 in (153.9 cm)                                                                                              |
| Width:                           | 30.2 in (76.7 cm)                                                                                               |
| Height:                          | 45.9 in (116.6 cm)                                                                                              |
| Weight:                          | 348.7 lbs (158.2 kg)                                                                                            |
| Carton Dimensions:               | 45.5 x 33 x 41 in (115.57 x 83.82 x 104.14 cm)                                                                  |

Warranty

|                |                                    |
|----------------|------------------------------------|
| Unit & Engine: | 1 Year Limited Commercial Warranty |
| Gear Case:     | 5 Year Limited Commercial Warranty |

Optional Accessories

|                                       |          |
|---------------------------------------|----------|
| Large Sno-Thro Cover.....             | 72601500 |
| 10 lb. Front Weight Kit.....          | 72406500 |
| Ariens Branded Snow Cab.....          | 72102600 |
| Non-Abrasive Skid Shoe Kit.....       | 72600300 |
| Sno-Thro Maintenance Kit.....         | 72101300 |
| Protective Floor Mat – 30” x 36”..... | 70707600 |
| Shear Bolt with Nut.....              | 52100100 |

# Power Brush 28

## Model Number: 921025

### Engine

|                         |                |
|-------------------------|----------------|
| Manufacturer:           | Subaru         |
| Horse Power:            | 6 hp           |
| Displacement:           | 169cc          |
| Starter:                | 120V/recoil    |
| High Idle: - RPM (min): | 3800+/-100     |
| Fuel Tank Capacity:     | 3.4 qt (3.6 L) |
| Oil Capacity:           | 20 oz. (.6 L)  |

### Brush Features

|                             |                           |
|-----------------------------|---------------------------|
| Clearing Width:             | 28 in (71.2 cm)           |
| Brush Diameter:             | 18 in (46 cm)             |
| Brush Rotation Angle:       | 20 degrees right/left     |
| Brush Rotation Control:     | Remote Trigger            |
| Brush Rotational Speed-RPM: | 200                       |
| Brush Caster Wheel:         | Adjustable                |
| Brush Caster Material:      | 3 in x 5 in Polypropylene |
| Interlock Control:          | No                        |
| Bristle Material:           | 6 in Polypropylene        |
| Hood:                       | 12 Gauge Steel            |

### Drive System

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Type:                 | Disc-O-Matic                                         |
| Speeds:               | 6 Forward / 2 Reverse                                |
| Axle System/Steering: | Automatic Traction Control                           |
| Tire Size/Type:       | 15 in x 5 in (38.1 x 12.7 cm) Directional Snow Tread |

### Additional Specifications

|                     |          |
|---------------------|----------|
| Halogen Headlight:  | No       |
| Handwarmers:        | No       |
| Electric Start:     | Standard |
| One Hand Interlock: | Standard |

### Dimensions

|                    |                                                |
|--------------------|------------------------------------------------|
| Length:            | 65 in (165.1 cm)                               |
| Width:             | 33 in (83.8 cm)                                |
| Height:            | 44 in (111.8 cm)                               |
| Weight:            | 230 lb (104.3 kg)                              |
| Carton Dimensions: | 65 x 38.5 x 35.5 in (165.1 x 97.79 x 90.17 cm) |

### Warranty

|                |                           |
|----------------|---------------------------|
| Unit & Engine: | 90-Day Limited Commercial |
|----------------|---------------------------|

### Optional Accessories

|                              |          |
|------------------------------|----------|
| Turf Caster Kit .....        | 72101200 |
| Tire Chains (16" x 8") ..... | 72101600 |
| Ariens Sno Cab .....         | 72102600 |

# Power Brush 36

## Model Number: 926062

### Engine

|                         |                |
|-------------------------|----------------|
| Manufacturer:           | Subaru         |
| Horse Power:            | 9 hp           |
| Displacement:           | 265cc          |
| Starter:                | 120V/recoil    |
| High Idle: - RPM (min): | 3800+/-100     |
| Fuel Tank Capacity:     | 6.1 L (6.3 qt) |
| Oil Capacity:           | 34 oz. (1.0 L) |

### Brush Features

|                             |                                   |
|-----------------------------|-----------------------------------|
| Clearing Width:             | 36 in (91.4 cm)                   |
| Brush Diameter:             | 25 in (64 cm)                     |
| Brush Rotation Angle:       | 20 degrees left/ 20 degrees right |
| Brush Rotation Control:     | Remote Trigger                    |
| Brush Rotational Speed-RPM: | 200                               |
| Brush Caster Wheel:         | Adjustable with tuft kit          |
| Brush Caster Material:      | 3 in x 5 in Polypropylene         |
| Interlock Control:          | Yes                               |
| Bristle Material:           | 7 in Polypropylene                |
| Hood:                       | 12 Gauge Steel                    |

### Drive System

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| Type:                 | Disc-O-Matic                                       |
| Speeds:               | 6 Forward / 2 Reverse                              |
| Axle System/Steering: | Automatic Traction Control                         |
| Tire Size/Type:       | 16 in x 6.5 in (41 x 17 cm) Directional Snow Tread |

### Additional Specifications

|                        |                 |
|------------------------|-----------------|
| Halogen Headlight:     | In-dash Halogen |
| Handwarmers:           | No              |
| Electric Start:        | Standard        |
| Commercial Handlebars: | Standard        |

### Dimensions

|                    |                                               |
|--------------------|-----------------------------------------------|
| Length:            | 72 in (182.9 cm)                              |
| Width:             | 44 in (111.8 cm)                              |
| Height:            | 43 in (109.2 cm)                              |
| Weight:            | 325 lb (147.4 kg)                             |
| Carton Dimensions: | 60 x 47.5 x 40 in (152.4 x 120.65 x 101.6 cm) |

### Warranty

|                |                           |
|----------------|---------------------------|
| Unit & Engine: | 1-Year Limited Commercial |
|----------------|---------------------------|

### Optional Accessories

|                                |          |
|--------------------------------|----------|
| Ariens Snow Cab .....          | 72102600 |
| Dirt Deflection .....          | 72602300 |
| Tire Chains (16" x 8") .....   | 72601800 |
| Steel Bristle Brush head ..... | 72602200 |

# Hydro Brush 36

## Model Number: 926518

### Engine

|                         |                      |
|-------------------------|----------------------|
| Manufacturer:           | Subaru               |
| Horse Power:            | 9.5 hp               |
| Displacement:           | 287cc                |
| Starter:                | 12V Key Start/recoil |
| High Idle: - RPM (min): | 3800+/-100           |
| Fuel Tank Capacity:     | 6.1 qt (6.3 L)       |
| Oil Capacity:           | 34 oz. (1.0 L)       |

### Brush Features

|                             |                                  |
|-----------------------------|----------------------------------|
| Clearing Width:             | 36 in (91.4 cm)                  |
| Brush Diameter:             | 25 in (64 cm)                    |
| Brush Rotation Angle:       | 20 degrees right/20 degrees left |
| Brush Rotation Control:     | Remote Trigger                   |
| Brush Rotational Speed-RPM: | 200                              |
| Brush Caster Wheel:         | Adjustable                       |
| Brush Caster Material:      | 3 in x 5 in Polypropylene        |
| Interlock Control:          | Yes                              |
| Bristle Material:           | 7 in Polypropylene               |
| Hood:                       | 12 Gauge Steel                   |

### Drive System

|                       |                                                                  |
|-----------------------|------------------------------------------------------------------|
| Type:                 | Hydrostatic, Hydro-Gear® RT 310™ transmission with synthetic oil |
| Speeds:               | Infinitely Variable                                              |
| Axle System/Steering: | Automatic Traction Control                                       |
| Tire Size/Type:       | 16 in x 6.5 in (41 x 17 cm) Directional Snow Tread               |

### Additional Specifications

|                        |          |
|------------------------|----------|
| Halogen Headlight:     | Standard |
| Handwarmers:           | Standard |
| Electric Start:        | Standard |
| Commercial Handlebars: | Standard |

### Dimensions

|                    |                                               |
|--------------------|-----------------------------------------------|
| Length:            | 72 in (182.9 cm)                              |
| Width:             | 44 in (111.8 cm)                              |
| Height:            | 43 in (109.2 cm)                              |
| Weight:            | 418 lbs (189.6 kg)                            |
| Carton Dimensions: | 60 x 47.5 x 40 in (152.4 x 120.65 x 101.6 cm) |

### Warranty

|                |                           |
|----------------|---------------------------|
| Unit & Engine: | 1-Year Limited Commercial |
|----------------|---------------------------|

### Optional Accessories

|                                |          |
|--------------------------------|----------|
| Ariens Snow Cab .....          | 72102600 |
| Dirt Deflection .....          | 72602300 |
| Tire Chains (16" x 8") .....   | 72601800 |
| Steel Bristle Brush head ..... | 72602200 |



# OUR **FAMILY PHOTO**

This is not just our family of Sno-Thros®. This is a force to be reckoned with. They all love to devour snow, because they all share the Ariens DNA. But each machine has its own unique set of powerful and purposeful characteristics. From sidewalks to big spreads. Light dustings to intimidating drifts. When faced with this opposition, Old Man Winter waves the white flag.



Time tested. Generation approved. For performance, durability, and power you'll be proud to pass on to the next generation—choose Ariens, the number one brand Sno-Thro worldwide.



Backed by an industry-leading 5-year warranty, the Ariens commercial-duty cast-iron gear case is a remarkably engineered component unique to Ariens Sno-Thro lineup.



Built to last from the handlebars to the housing. Every Ariens 2-stage Sno-Thro features all-steel construction so you can overcome winter's relentless conditions for years to come.



Unsurpassed design. Unrivaled guarantees. Every Ariens product comes backed by a 3-year warranty supported by an extensive independent dealer network.

**VISIT US ONLINE AT: [ARIENS.COM](http://ARIENS.COM)**

FOR PRODUCT INFORMATION, CUSTOMER REVIEWS,  
PRODUCT VIDEOS, DEALER LOCATOR AND CUSTOMER SUPPORT.



**ARIENS**  
THE KING OF SNOW



© Registered trademark and TM trademark of Ariens Company, Briggs & Stratton® and Hydro-Gear® are registered trademarks of their respective companies. Sno-Thru unit specifications and features are subject to change without notice. Photos are a representation, actual product may differ.

© 2016 ARIENS COMPANY. ALL RIGHTS RESERVED.

An *Ariens* Company Brand